



1. Product and company identification

Product name	Castrol 50/50 Extended Life Coolant
MSDS #	466522
Code	466522-US85
Product use	Coolant and antifreeze. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION:	1 (800) 447-8735 Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

2. Hazards identification

Physical state	Liquid.
Color	Not available.
Emergency overview	WARNING ! HARMFUL IF SWALLOWED. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. Harmful if swallowed. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects	
Eyes	Causes eye irritation.
Skin	Causes skin irritation.
Inhalation	Vapors may cause drowsiness and dizziness. Can cause central nervous system (CNS) depression. May cause respiratory tract irritation.
Ingestion	Harmful if swallowed. Causes gastrointestinal irritation and diarrhea.

[See toxicological information \(section 11\)](#)

Product name Castrol 50/50 Extended Life Coolant	Product code 466522-US85	Page: 1/6
Version 1	Date of issue 03/02/2009.	Format US
	(US)	Language ENGLISH. (ENGLISH)

3. Composition/information on ingredients

Ingredient name	CAS #	%
Ethylene glycol; ethanediol	107-21-1	90 - 95
Diethylene glycol; 2,2'-oxybisethanol	111-46-6	1 - 5

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Inhalation	If inhaled, remove to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

Flash point	Closed cup: 119°C (246.2°F) [Setaflash.]
Fire/explosion hazards	In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	Use an extinguishing agent suitable for the surrounding fire.
Not suitable	Do not use water jet.
Fire-fighting procedures	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous combustion products	Combustion products may include the following: phosphorus oxides metal oxide/oxides carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)
Protective clothing (fire)	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product name	Castrol 50/50 Extended Life Coolant	Product code	466522-US85	Page:	2/6
Version	1	Date of issue	03/02/2009.	Format	US
					(US)
				Language	ENGLISH.
					(ENGLISH)

7. Handling and storage

Handling	Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
Storage	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Ethylene glycol; ethanediol

Occupational exposure limits

ACGIH TLV (United States).

C: 100 mg/m³ Issued/Revised: 5/1995 Form: Aerosol

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Personal protection

Eyes Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body Do not get on skin or clothing. Wear suitable protective clothing.

Respiratory Use adequate ventilation. Do not breathe vapor or mist.

Hands The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling instructions.

9. Physical and chemical properties

Physical state	Liquid.
Flash point	Closed cup: 119°C (246.2°F) [Setaflash.]
Specific gravity	1.12
pH	11 [Conc. (% w/w): 50%]
Boiling point / Range	171 to 175°C (339.8 to 347°F)
Melting point / Range	-18°C (-0.4°F)
Volatility	97% (v/v)
Solubility	Soluble in water.

Product name Castrol 50/50 Extended Life Coolant

Product code 466522-US85

Page: 3/6

Version 1 **Date of issue** 03/02/2009.

Format US
(US)

Language ENGLISH.
(ENGLISH)

10. Stability and reactivity

Stability and reactivity	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Other Toxicity Data

Ethylene glycol: Ingestion of ethylene glycol can cause metabolic acidosis, kidney damage, central nervous system depression, convulsions and death. The estimated human lethal dose is approximately 1 ml/kg (about 1/2 cup for an adult). Vapor from hot operations or an aerosol can cause eye and respiratory irritation. Birth defects were reported in laboratory animals fed ethylene glycol repeatedly in large amounts. Based on these studies, there may be a potential for birth defects following ingestion of ethylene glycol by pregnant women.

Long-term overexposure: May cause respiratory irritation.

Other information

Potential chronic health effects

Carcinogenicity

No known significant effects or critical hazards.

Medical conditions aggravated by over-exposure

Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

12. Ecological information

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

Product name Castrol 50/50 Extended Life Coolant

Product code 466522-US85

Page: 4/6

Version 1 **Date of issue** 03/02/2009.

Format US

Language ENGLISH.

(US)

(ENGLISH)

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Ethylene glycol; ethanediol; Diethylene glycol; 2,2'-oxybisethanol

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol 50/50 Extended Life Coolant: Immediate (acute) health hazard, Delayed (chronic) health hazard

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Ethylene glycol; ethanediol	107-21-1	90 - 94.99
Supplier notification	Ethylene glycol; ethanediol	107-21-1	90 - 94.99
CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):	CERCLA: Hazardous substances.: Ethylene glycol; ethanediol: 5000 lbs. (2270 kg);		

State regulations

Massachusetts Substances

The following components are listed: ETHYLENE GLYCOL

New Jersey Hazardous Substances

The following components are listed: ETHYLENE GLYCOL

Pennsylvania RTK Hazardous Substances

The following components are listed: 1,2-ETHANEDIOL; ETHANOL, 2,2'-OXYBIS-

California Prop. 65

California Prop 65: No products were found

Inventories

Canada inventory

All components are listed or exempted.

Europe inventory

All components are listed or exempted.

Australia inventory (AICS)

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

At least one component is not listed.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

16. Other information

Label requirements

WARNING !

HARMFUL IF SWALLOWED.
INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS.
CAUSES EYE AND SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Product name Castrol 50/50 Extended Life Coolant

Product code 466522-US85

Page: 5/6

Version 1 **Date of issue** 03/02/2009.

Format US

Language ENGLISH.

(US)

(ENGLISH)

HMIS® Rating :

Health * 2
 Flammability 1
 Physical Hazard 0
 Personal protection X

National Fire Protection Association (U.S.A.)

**History**

Date of issue 03/02/2009.
Date of previous issue No previous validation.
Prepared by Product Stewardship

Notice to reader

NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name Castrol 50/50 Extended Life Coolant

Product code 466522-US85

Page: 6/6

Version 1 **Date of issue** 03/02/2009.

Format US
(US)

Language ENGLISH.
(ENGLISH)