

Material Safety Data Sheet



1. Chemical product and company identification

Product name CASTROL UNIVERSAL TRACTOR FLUID
MSDS # 0000002628
Code 0000002628
Product use Hydraulic fluid / Transmission fluid
For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: (973) 633-2200
Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION 1 (866) 4 BP - MSDS
(866-427-6737 Toll Free - North America)
email: bpcares@bp.com

2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Base oil - highly refined	64741-88-4	85 - 90
Base oil - highly refined	proprietary	5 - 10
Zinc alkyl dithiophosphate	68649-42-3	1 - 5

3. Hazards identification

Physical state Liquid.
Color Amber.
Emergency overview WARNING!
CAUSES SKIN IRRITATION.
MAY CAUSE EYE IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects
Eyes May cause eye irritation.
Skin Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. High pressure skin injections are serious medical emergencies. Injury will not appear serious at first; within a few hours, tissue will become swollen, discolored and extremely painful.

Inhalation	May cause respiratory tract irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.
Medical conditions aggravated by over-exposure	None identified.
See toxicological information (section 11)	

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Accidental high pressure injection through the skin requires immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

5. Fire-fighting measures

Flammability of the product	May be combustible at high temperature.
Flash point	215 °C (Open cup)
Products of combustion	These products are carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide), sulfur oxides (SO ₂ , SO ₃ etc.), oxides of phosphorus, other hazardous substances.
Unusual fire/explosion hazards	This material is not explosive as defined by established regulatory criteria.
Fire-fighting media and instructions	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.
Protective clothing (fire)	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Environmental precautions and clean-up methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

7. Handling and storage

Handling	Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Product name	CASTROL UNIVERSAL TRACTOR FLUID	MSDS #	0000002628	Page: 2/5
Version 2	Date of issue 04/26/2006.	Format US	Language ENGLISH.	
			(ENGLISH)	
Build 4.2.7				

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Base oil - highly refined

Occupational exposure limits

ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Zinc alkyl dithiophosphate

None assigned.

Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes

Avoid contact with eyes. Chemical splash goggles.

Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

Wear suitable gloves.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state

Liquid.

Color

Amber.

Heat of combustion

Not available.

Pour Point

-37 °C

Specific gravity

0.8856

Solubility

Insoluble in cold water.

Viscosity

Kinematic: 55.89 mm²/s (55.89 cSt) at 40°C

Kinematic: 9.39 mm²/s (9.39 cSt) at 100°C

SUS: 284.9 SUS at 37.8°C

Viscosity Index

151

10. Stability and reactivity

Stability and reactivity

The product is stable.

Conditions to avoid

Keep away from heat, sparks and flame.

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition products

Products of combustion: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide), sulfur oxides (SO₂, SO₃ etc.), oxides of phosphorus, other hazardous substances.

Hazardous polymerization

Will not occur.

Product name CASTROL UNIVERSAL TRACTOR FLUID

MSDS # 0000002628

Page: 3/5

Version 2

Date of issue 04/26/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)

11. Toxicological information

Chronic toxicity

Carcinogenic effects	No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).
Mutagenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.
Reproductive effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.
Teratogenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations US INVENTORY (TSCA): In compliance.

TSCA 12(b) one-time export notification:: nonane

TSCA 12(b) annual export notification: Lead

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: CASTROL

UNIVERSAL TRACTOR FLUID: Immediate (Acute) Health Hazard

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Zinc alkyl dithiophosphate	68649-42-3	1.208 - 1.806
Supplier notification	Zinc alkyl dithiophosphate	68649-42-3	1.208 - 1.806

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Zinc alkyl dithiophosphate; Arsenic: 1 lbs. (0.4536 kg); Cadmium: 10 lbs. (4.536 kg); Lead: 10 lbs. (4.536 kg);

State regulations

New Jersey: Zinc alkyl dithiophosphate

Pennsylvania RTK: Zinc alkyl dithiophosphate (environmental hazard, generic environmental hazard)

Product name CASTROL UNIVERSAL TRACTOR FLUID

MSDS # 0000002628

Page: 4/5

Version 2

Date of issue 04/26/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)

WARNING: This product contains a chemical known to the State of California to cause cancer.
Arsenic

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
Cadmium; Lead

Inventories

AUSTRALIAN INVENTORY (AICS): In compliance.

CANADA INVENTORY (DSL): In compliance.

CHINA INVENTORY (IECS): In compliance.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (ENCS): In compliance.

KOREA INVENTORY (ECL): In compliance.

PHILIPPINE INVENTORY (PICCS): In compliance.

16. Other information

Label requirements

WARNING!

CAUSES SKIN IRRITATION.
MAY CAUSE EYE IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health 2 -
Flammability 1
Physical Hazard 0
Personal protection X

National Fire Protection Association (U.S.A.)



History

Date of issue 04/26/2006.

Date of previous issue 04/26/2006.

Prepared by Product Stewardship

Notice to reader

NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name CASTROL UNIVERSAL TRACTOR FLUID

MSDS # 0000002628

Page: 5/5

Version 2 **Date of issue** 04/26/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)