



4250 Williams Road, San Jose, California 95129-3344
Office: 408-252-7720 Plant: 408-251-0810
Developers and Manufacturers of Fine Petroleum Products Since 1935



PRODUCT INFORMATION

COAST GAS ENGINE OIL SAE 40

Coast Gas Engines Oil is the preferred product for engines with high compression ratios and turbo charge, and two-stroke engines known to be sensitive to combustion chamber and port deposits. Recommended for two stroke and selected four strokes stationary engines that use natural gas or synthetic gas as fuel.

TYPICAL TEST DATA

APPEARANCE	Dark Pale
GRAVITY API	30.1
FLASH COC, °F	480 (248)
POUR POINT, °F	6.8 -(14)
SULFATED ASH WT %	.02 MAX
CST AT 100°C	135
CST AT 40°C	13.4
SUS AT 100°F	790
SUS AT 210°F	75
VISCOSITY INDEX	95

APPLICATIONS: Suitable as service fill for the following major Gas Engine Manufacturers:

Ajax
Caterpillar (except 3400, 3500, 3600)
Clark - Dresser
Cooper - Bessemer (two-stroke)
Dresser - Rand (IR) Categories I & II
Fairbanks - Morse/MEP
Waukesha VR & Intermediate/Clinton
Worthington (two-stroke)

DISPOSAL: Used oil must be handled with caution and should be sent for recycling.

MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720