



4250 Williams Road, San Jose, California 95129-3344  
Office: 408-252-7720 Plant: 408-251-0810  
Developers and Manufacturers of Fine Petroleum Products Since 1935



## PRODUCT INFORMATION

### COAST ULTRA 5W-20

Coast Ultra 5W-20 is a premium quality crankcase lubricate blended from high quality re-refined high viscosity index base oils with GF-4 energy conserving additives. Coast Ultra 5W-20 motor oil using the latest high quality base stocks and GF-4 additive package is formulated to meet the performance requirements of ILSAC GF-4 and API SM.

#### TYPICAL TEST DATA

SAE GRADE	5W-20
APPEARANCE	STRAW
GRAVITY API	32.5
FLASH PT(PMCC), °F	<170
POUR PT, °F	-45
TBN	7.3
VISCOSITY CP At - 35C°	6000
CST AT 100C°	8.8
CST AT 40C°	52
SUS AT 100C°	254
SUS AT 210C°	60.1
Volatility	
D5800	15% MAX
D6417	10% MAX
% Recycled / Re-refined	85 %

**APPLICATIONS:** Coast Ultra 5W-20 motor oil be recommended for the following:  
ILSAC GF-4, GF-3, GF-2 and GF-1 Oils are required.

API SM, SL, SJ, SH, SG, SF and SE oils are required- Energy Conserving

Ford M2C-153H/G/F/E oils are required.

All gasoline engine requiring SAE 5W-20 viscosity motor oils including many of the new Honda, Ford, and Mazda autos.

**DISPOSAL:** Used oil must be handled with caution and should be sent for recycling.

**Products not recommended for two cycle and aircraft gasoline engine.**

**MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720**