



4250 Williams Road, San Jose, California 95129-3344
 Office: 408-252-7720 Plant: 408-251-0810
 Developers and Manufacturers of Fine Petroleum Products Since 1935



PRODUCT INFORMATION

COAST ULTRA AUTOMATIC TRANSMISSION FLUID

A new generation automatic transmission fluid recommended for service in domestic and foreign motor vehicle automatic and powershift trans-missions. The product meets or exceeds requirements for Dexron III® and Mercon® trademark transmission fluids.

TYPICAL TEST DATA

APPEARANCE	RED DYED
GRAVITY API	36
FLASH PMCC (°C)	>170
POUR POINT, (°C)	-41
VISCOSITY CP AT -40°C	16500
CST AT 100°C	7.3
CST AT 40°C	36.1
SUS AT 100°F	187
SUS AT 210°F	56
VISCOSITY INDEX	169
% RECYCLED / RE-REFINED	88

APPLICATIONS: Suitable as service fill for the following major auto and industrial machinery manufacturers:

- | | |
|---------------------------------|---|
| General Motors | Caterpillar TO-2 |
| Daimler – Benz Car & Commercial | Allision Hydraulic Transmission C-4, C-3 |
| Ford - M2C166-11 M2C138-CJ | Sperry-Vickers Mobile Hydraulics M-2950-S and I-286-S |
| Chrysler | Hagglunds-Denison H.F.O. |
| Nissan | Honda |
| Toyota | Voith DIWA Transmissions |
- Suitable for low temperature hydraulic and rotary compressor fluid.

DISPOSAL: Used oil must be handled with caution and should be sent for recycling.

MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING 408-252-7720.

© Registered Trademark 40893