



4250 Williams Road, San Jose, California 95129-3344
 Office: 408-252-7720 Plant: 408-251-0810
 Developers and Manufacturers of Fine Petroleum Products Since 1935



P R O D U C T I N F O R M A T I O N

COAST ULTRA MOTOR OILS

COAST ULTRA MOTOR OILS are specifically formulated premium quality re-refined oils meeting the most demanding lubrication requirements for virtually all diesel and gasoline engines. Coast Ultra Engine Oils provide flow at low temperatures, high viscosity for high temperatures, superior detergent/ dispersant additives, and friction reducing properties to promote superior engine life and performance.

TYPICAL TEST DATA

SAE GRADE	5w30	10w30	10w40	20w50@	30	40 @
APPEARANCE	Pale	Pale	Pale	Pale	Pale	Pale
GRAVITY API	32	31	29.2	29.6	27.2	26.8
FLASH COC, °F	410	410	420	435	430	460
POUR PT, °F	-38	-35	-35	-26	0	15
VISCOSITY						
CST AT 100C	10.4	10.4	14.5	18	11.3	14.4
CST AT 40C	63	68	99	163	96	135
CP AT -20C-CCV		3000	3200			
CP AT -10C-CCV				4300		
CP AT -25C-CCV	3200					
VISCOSITY INDEX	160	145	160	130	105	108
%RECYCLED RE-REFINED	78	75	74	70	75	64

APPLICATIONS: Formulated to meet or exceed industry requirements.

API Service Classifications SM- 5W-30, 10W-30, 10W-40

ILSAC Oil Specification GF-4-5w30 10W-30

Energy Conserving 5W-30, 10W-30

@ SAE 40 API- CF, CG-4, CH-4

@ SAE 20W-50 API SL

Manufacturers Performance Requirements: Ford ESE-M2C153-C (SAE 5w30, 10w-30),

Nissan Ka 24e, WSS- M2C153- F (SAE 5w-30, 10w-30)

General Motors GM 9986125 (SAE 5w30) GM 9986126 (SAE 10w30)

DISPOSAL: Used oil must be handled with caution and should be sent for recycling.

CERTIFICATION: Coast Ultra Motor Oils contain by volume re-refined base oil that will meet government requirements for the affirmative purchase of lubricating products (Coast 20W-50@ & 40@) Does not meet California State Agency buy Recycled.

MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720