



4250 Williams Road, San Jose, California 95129-3344  
 Office: 408-252-7720 Plant: 408-251-0810  
 Developers and Manufacturers of Fine Petroleum Products Since 1935



**P R O D U C T I N F O R M A T I O N**

**COAST Ultra TFD FLUID**

Coast Ultra TFD Fluid is formulated to perform at higher operating temperatures. The product provides improved friction and anti-wear performance compared to TO-2 fluids. Coast Ultra TFD Fluid should be used whenever a product meeting the Caterpillar TO-4 specification is required. SAE 30 grade can be used in applications requiring an Allison C-4 product. Coast Ultra products are blended with special group of recycled rerefined base oils to meet industry standards.

**TYPICAL TEST DATA**

SAE OR GRADE	30	50
APPEARANCE	Pale	Dark Pale
GRAVITY API	25.6	24.3
FLASH COC, °F	450	470
POUR PT, °C	-10	-17.8
VISCOSITY		
SUS AT 100°F	530	1220
SUS AT 210°F	62	95.9
CST AT 40°C	100.1	231
CST, AT 100°C	10.9	18.9
VISCOSITY INDEX	93	92
Recycled re-refined	66	42

**APPLICATIONS:**Meets requirements of the Caterpillar TO-4 specification. SAE 30 grade recommended for Allison C-4 applications. Recommended for Komatso Dresser construction equipment.

Coast Ultra TFD Fluid cannot be used in farm tractors or other applications where wet brakes and clutches are used. Updated 6.7.07.

Disposal: used oil must be handled with caution and should be sent for recycling.

**MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720 or [www.coastoil.com](http://www.coastoil.com)**